Panasonic

TOUGHBOOK C2

- 12.5" Convertible Tablet with Multi Touch or Multi Touch + Digitizer Display
- Daylight-readable 500 Nit IPS Display
- Rugged Triple Hinge Design
- Full Shift Battery Life
- Bridge Battery Enables Hot-swap Battery Replacement for Continuous Use
- Available NFC, Bottom Camera, Serial Port and SmartCard Reader



Panasonic recommends Windows 8.





Longest standard battery life in its class.

The Panasonic Toughbook® C2 provides an amazing 14 hours of battery life (19 hours with optional long life battery) and weighs 3.99 lbs. The 12.5" convertible tablet features an array of industry-leading advancements, such as being the only convertible tablet in its class to offer a durable triple hinge design, as well as a unique bridge battery for continuous use by enabling hot-swappable battery replacement without disruption. The Toughbook C2 has an incredibly bright and sharp 500 nit IPS display with direct bonding for wider viewing angles and a lighter design. The ergonomic strap is perfect for long-term use and holding the PC in any orientation. Available integrated options, such as a SmartCard reader, NFC, bottom camera and serial port, make the Toughbook C2 ideal for a wide variety of applications and environments.

TOUGHBOOK



Panasonic recommends Windows 8.

DURABILITY	 2.5' drop rating from 6 sides (1' from remaining sides) Spill registrant keyhaard 		
 Spill-resistant keyboard Magnesium alloy case with hand strap 			
	 Rugged triple hinge design 		
	Shock-mounted flex-connect hard drive with quick-release		
SOFTWARE	Pre-installed replaceable screen film for display protection		
DUFIWARE	 Windows[®] 8.1 Pro, Windows[®] 7 Professional Panasonic Utilities (including Dashboard), Recovery Partition 		
CPU	 Intel® Core™ i5-4300U vPro™ Processor - 1.9GHz with Turbo Boost up to 2.9GHz 		
	– 4th generation		
	– 3MB cache		
STORAGE & MEMORY	4GB or 8GB SDRAM (DDR3L) ^{1,2}		
	 500GB 7200rpm hard drive (shock-mounted flex-connect with – Optional 128GB and 256GB reinforced flex-connect SSD² 	quick-release)²	
ISPLAY	 12.5" HD 1366 x 768 with LED backlighting 		
	 – 5-point capacitive multi touch + digitizer 		
	- 5-point capacitive multi touch		
	 2-500 nit IPS display with direct bonding 		
	 Anti-reflective and anti-glare screen treatments 		
	Ambient light, magnetic, gyro and acceleration sensors		
	 Automatic screen rotation Intel[®] HD Graphics 4400, max. 1792MB shared VRAM with Win 	8.1 64-bit ³	
	 Dual monitor support through HDMI and/or optional VGA 		
	 Concealed mode (configurable) 		
UDIO	Integrated microphone		
	 Intel[®] high-definition audio compliant Integrated speaker 		
	 Keyboard volume and mute controls 		
(EYBOARD & INPUT	Touch and gestures		
	 Stylus pen with integrated stylus holder 		
	 6 tablet buttons (2 user-definable) 		
	 Dashboard 84-key with dedicated Windows[®] key 		
	 Oversized electrostatic touchpad with multi touch support 		
CAMERAS	 HD 960p webcam with mic and camera on/off indicator Optional 5MP bottom camera with auto focus⁴ 		
	= Optional 3MP bottom camera with auto locus		
EXPANSION SLOTS	 ExpressCard/34 SD card (SDXC) 		
NTERFACE	Docking connector 100-pin		
	HDMI Type A		
	■ Optional VGA ⁵ D-sub 15-pin		
	 Headphones/speaker Mini-jack stereo Microphone/line in Mini-jack stereo 		
	■ Optional serial ⁵ D-sub 9-pin		
	USB 3.0 (x 2), USB 2.0 (x 1) 4-pin		
	 ■ 10/100/1000 Ethernet RJ-45 ■ Optional 56K Modem⁵ RJ-11 		
WIRELESS		h catallita CDS	
WINELEJJ	 Optional integrated 4G LTE multi carrier mobile broadband wit Optional NFC (Near Field Communications)⁴ 	n satettite UPS	
	 Intel[®] Dual Band Wireless-N 7260 802.11a/b/g/n 		
	 Bluetooth® v4.0 + EDR (Class 1) Converte 		
	 Security Authentication: LEAP, WPA, 802.1x, EAP-TLS, EAP-FAST, PE/ 	ΔP	
	 – Autoentication: EEAP, WPA, 802.13, EAP-1E3, EAP-PAST, EE – Encryption: CKIP, TKIP, 128-bit and 64-bit WEP, Hardware Al 		
	 Slide on/off switch 		
POWER SUPPLY	Li-lon battery pack with bridge battery:		
	- Standard battery ⁶ : 10.8V, typical 6800mAh, minim		
	 Long life battery: 10.8V, typical 9300mAh, minim Lightweight battery⁷: 10.8V, typical 3400mAh, minim 		
	 Battery operation⁸: 		
	- Standard battery ⁶ : 14 hours		
	– Long life battery: 19 hours – Lightweight battery ⁷ : 7 hours		
	– Lightweight battery ⁷ : 7 hours – Bridge battery: 1 minute		
	 Battery charging time⁸: 2.5 hours off, 3 hours on (standard) 		
	3 hours off, 3.5 hours on (long		
	2 hours off, 2.5 hours on (light AC Adapter: AC 100V-240V 50/60Hz, auto sensing/switching wo		
	 Battery status and bridge battery LED indicators 		
POWER MANAGEMENT	 Suspend/Resume Function, Hibernation, Standby, ACPI BIOS 		
· · · · · · · · · · · · · · · · · · ·	 Suspend/resume ranction, inbernation, standby, ACFI DIOS 		





SECURITY FEATURES Password Security: Supervisor, User, Hard Di Kensington cable lock slot Trusted platform module (TPM) security chip Computrace® theft protection agent in BIOS® Intel® Anti-Theft Technology Optional fingerprint reader Optional SmartCard reader ¹⁰	
WARRANTY S-year limited warranty, parts and labor	
DIMENSIONS & WEIGHT 8.4"[L] x 11.8"[W] x 1.0"/1.7"[H] front/rear 3.72 lbs. (lightweight battery] ⁷ 3.99 lbs. (standard battery] ⁶ 4.28 lbs. (long life battery)	
INTEGRATED OPTIONS ¹¹ 46 LTE multi carrier mobile broadband with s Choice of Serial ⁵ or VGA ⁵ or Modem ⁵ Choice of SmartCard ¹⁰ or NFC ⁴ or 5MP botto Fingerprint reader Lightweight battery Long life battery 1280B and 2560B solid state drives (SSD)	
SELECT ACCESSORIES ¹¹ AC Adapter (3-prong) Standard Battery Pack Lightweight Battery Pack Long Life Battery Pack Battery Charger LIND 3-Bay Battery Charger LIND 3-Bay Battery Charger LIND Car/AC Adapter 120W LIND Car/AC Adapter 90W (with USB port) ToughMate C2 Shoulder Strap ToughMate C2 Shoulder Strap ToughMate CamUniversal Carrying Case ToughMate Backpack Memory Card 4GB DDR3 Desktop Dock with DVD Drive Multi Touch Replacement Stylus Multi Touch + Digitizer Replacement Stylus Tether 12.5" LCD Protective Film	CF-AA6413CM CF-VZSU80U CF-VZSU83U CF-VZSU83U CF-VCBTB3W CF-LND3BAYC2 CF-LNDACDC90 TBCC2CASE-P TBCC2CASE-P TBCC2CMUNV-P TBCBPK-K CF-WMBA1204G CF-VEBC21U CF-VNP020AU CF-VNP016AU CF-VNP016AU CF-VNP04U CF-VNP04U

Please consult your reseller or Panasonic representative before purchasing.
¹ Total usable memory will be less depending upon actual system configuration.
² 1GB = 1,000,000 bytes.
³ The size of the VRAM cannot be set by the user and varies by operating system as well as size of RAM. Windows 7 max. VRAM is 1696MB.
SmartCard reader, NFC and 5MP bottom camera are mutually exclusive.
⁵ Serial, VGA and modem ports are mutually exclusive.
*Comes with multi touch + digitizer model.
⁷ Comes with multi touch model.
Approximate time. Battery performance features such as charge time and life span can vary according to the conditions under which the computer and battery are used. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other customer preferences. Battery testing results from MobileMark 2007.
*Requires software and activation to enable theft protection.
¹⁰ Half size on models with ExpressCard. Full size on models without ExpressCard.
¹¹ Accessories and Integrated Options may vary depending on your notebook configuration. Visit Panasonic website for more accessories and details.
www.mruggedmobile.com

www.mruggedmobile.com sales@mruggedmobile.com 847-870-3805

SOLUTIONS FOR BUSINESS

Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. ©2013 Panasonic Corporation of North America. All rights reserved. Toughbook C2 Spec Sheet_11/13

