

Panasonic recommends Windows.

Panasonic



TOUGHPAD FZ-G1

- 4th Generation Intel® Core™ i5 vPro™ Processor
- Daylight-readable Display with Gloved Multi Touch + Digitizer
- Up to 20 Hours of Use with an Optional Long Life Battery¹
- Integrated Bridge Battery, SmartCard, 2D Barcode, Magstripe, RFID, Serial Options and More^{2,3}
- Certified for Use in Hazardous Locations (Class I Division 2)⁴
- 3-year Warranty with Business Class Support

4-FOOT
DROP RATING

IP65

MIL-STD-810G

THE WORLD'S THINNEST AND LIGHTEST FULLY-RUGGED 10.1" WINDOWS® 8.1 PRO TABLET.

The Toughpad® FZ-G1 Windows® 8 tablet offers a fluid user experience while providing crucial port connectivity and feature rich options in a compact size. Designed for highly mobile field workers, it's the thinnest and lightest fully-rugged 10.1" tablet running Windows® 8. Powered by an Intel® Core™ i5 vPro™ processor with a MIL-STD-810G and IP65 certified design, the Toughpad FZ-G1 Windows® 8 tablet leads the way in rugged mobile computing. Add to that an HD daylight-readable 10-point gloved multi touch + digitizer screen, and it becomes an essential tool for field workers.



847-870-3805 . sales@mruggedmobile.com
www.mruggedmobile.com/panasonic-toughpad-fz-g1-windows-tablet.aspx

TOUGHPAD®

TOUGHPAD FZ-G1

Panasonic

Panasonic recommends Windows.

SOFTWARE	<ul style="list-style-type: none"> Windows® 8.1 Pro 64-bit (available Windows® 7 Professional downgrade option) Panasonic Utilities (including Dashboard), Recovery Partition 														
DURABILITY	<ul style="list-style-type: none"> MIL-STD-810G certified (4' drop, shock, vibration, rain, dust, sand, altitude, freeze/thaw, high/low temperature, temperature shock, humidity, explosive atmosphere) IP65 certified sealed all-weather design Optional class I division 2, groups ABCD certified model Solid state drive heater Magnesium alloy chassis encased with ABS and elastomer corner guards Optional rotating hand strap Port covers Raised bezel for LCD impact protection Pre-installed replaceable screen film for LCD protection 														
CPU	<ul style="list-style-type: none"> Intel® Core™ i5-4310U vPro™ Processor <ul style="list-style-type: none"> 2.0GHz with Turbo Boost up to 3.0GHz Intel Smart Cache 3MB 														
STORAGE & MEMORY	<ul style="list-style-type: none"> 8GB^{5,6} <ul style="list-style-type: none"> Up to 64GB additional with optional microSD card Optional 128GB and 256GB solid state drives (SSD) with heaters^{5,6} Optional 128GB and 256GB Self Encrypting Drives (Opal specification) (Available Summer 2014)^{5,6} 														
DISPLAY	<ul style="list-style-type: none"> 10.1" WUXGA 1920 x 1200 with LED backlighting 10-point capacitive multi touch + digitizer daylight-readable screen <ul style="list-style-type: none"> 2-800 nit IPS display with direct bonding Anti-reflective and anti-glare screen treatments Ambient light sensor, digital compass, gyro and acceleration sensors Automatic screen rotation Intel® QM77 video controller, max. 1792MB shared VRAM with Win 8 64-bit⁷ Concealed mode (configurable) 														
AUDIO	<ul style="list-style-type: none"> Integrated microphone Realtek high-definition audio Integrated speaker On-screen and button volume and mute controls 														
KEYBOARD & INPUT	<ul style="list-style-type: none"> 10-point multi touch + digitizer screen <ul style="list-style-type: none"> Supports bare hand touch and gestures and electronic stylus pen Supports glove mode and wet touch mode 7 tablet buttons (2 user-definable) Integrated stylus holder On-screen QWERTY keyboard 														
CAMERAS	<ul style="list-style-type: none"> 720p webcam with mic 8MP rear camera with auto focus and LED light 														
EXPANSION	<ul style="list-style-type: none"> Optional MicroSD⁵ 														
INTERFACE	<table border="0"> <tr> <td>Docking connector</td> <td>24-pin</td> </tr> <tr> <td>HDMI</td> <td>Type A</td> </tr> <tr> <td>Headphones/speaker</td> <td>Mini-jack stereo</td> </tr> <tr> <td>Optional Serial Dongle³</td> <td>D-sub 9-pin</td> </tr> <tr> <td>USB 3.0 (x 1)^{2,3}</td> <td>4-pin</td> </tr> <tr> <td>Optional 2nd USB 2.0²</td> <td>4-pin</td> </tr> <tr> <td>Optional 10/100/1000 Ethernet³</td> <td>RJ-45</td> </tr> </table>	Docking connector	24-pin	HDMI	Type A	Headphones/speaker	Mini-jack stereo	Optional Serial Dongle ³	D-sub 9-pin	USB 3.0 (x 1) ^{2,3}	4-pin	Optional 2nd USB 2.0 ²	4-pin	Optional 10/100/1000 Ethernet ³	RJ-45
Docking connector	24-pin														
HDMI	Type A														
Headphones/speaker	Mini-jack stereo														
Optional Serial Dongle ³	D-sub 9-pin														
USB 3.0 (x 1) ^{2,3}	4-pin														
Optional 2nd USB 2.0 ²	4-pin														
Optional 10/100/1000 Ethernet ³	RJ-45														
WIRELESS	<ul style="list-style-type: none"> Optional integrated 4G LTE multi carrier mobile broadband with satellite GPS Optional GPS (U-blox 8)² Intel® Dual Band Wireless AC7260 Wi-Fi 802.11a/b/g/n/ac Bluetooth® v4.0 (Class 1) + EDR Security <ul style="list-style-type: none"> Authentication: LEAP, WPA, 802.1x, EAP-TLS, EAP-FAST, PEAP Encryption: CKIP, TKIP, 128-bit and 64-bit WEP, Hardware AES Dual high-gain antenna pass-through 														
POWER SUPPLY	<ul style="list-style-type: none"> Li-Ion battery pack: <ul style="list-style-type: none"> Standard battery: 10.8V, typical 4400mAh, minimum 4100mAh) Long life battery⁸: 10.8V, typical 9300mAh, minimum 8700mAh) Battery operation¹: <ul style="list-style-type: none"> Standard battery: 10 hours Optional long life battery⁸: 20 hours Battery charging time¹: <ul style="list-style-type: none"> Standard battery: 2.5 hours off, 3 hours on Optional long life battery¹: 3 hours off, 4 hours on Optional 7.5Wh bridge battery (10 minute swap time) 														
POWER MANAGEMENT	<ul style="list-style-type: none"> Suspend/Resume Function, Hibernation, Standby 														
SECURITY FEATURES	<ul style="list-style-type: none"> Password Security: Supervisor, User, Hard Disk Lock Kensington cable lock slot Trusted platform module (TPM) security chip v.1.2 Computrace® theft protection agent in BIOS⁹ Intel® Anti-Theft Technology Insertable SmartCard reader^{2,8} <ul style="list-style-type: none"> ISO 15693 and 14443 A/B compliant 														
WARRANTY	<ul style="list-style-type: none"> 3-year limited warranty, parts and labor 														
DIMENSIONS & WEIGHT¹⁰	<ul style="list-style-type: none"> 10.6"(L) x 7.4"(W) x 0.8"(H) 2.4 lbs. (standard battery) 3.0 lbs. (optional long life battery)⁸ 														

INTEGRATED OPTIONS¹¹

- 4G LTE multi carrier mobile broadband with satellite GPS
- Choice of 1D/2D barcode reader (EA11 or EA21), GPS (U-blox 8), Serial Dongle, Ethernet, MicroSD or 2nd USB 2.0 port³
- Choice of bridge battery, magstripe reader, insertable SmartCard reader, contactless SmartCard reader or UHF 900MHz RFID reader (EPC Gen 2)⁷

HAZARDOUS LOCATION CERTIFICATIONS¹²

- ANSI / ISA 2.12.01-2013
 - Optional Class I division 2, groups ABCD certified model

ACCESSORIES¹¹

- | | |
|--|--|
| <ul style="list-style-type: none"> AC Adapter (3-prong) Standard Battery Pack Long Life Battery Pack⁸ Long Life Battery Bundle (includes rotating hand strap and corner guard set) Single Battery Charger Bundle LIND 3-Bay Battery Charger LIND Car Adapter 120W LIND Car/AC Adapter 90W (with USB port) LIND Car Adapter 90W MIL-STD Tall Corner Guard Set Rotating Hand Strap and Corner Guard Set Bundle ToughMate G1 Always-on Case (w/hand strap) ToughMate G1 Professional Portfolio ToughMate G1 "X" Hand Strap Desktop Cradle Vehicle Docks (no pass-through) <ul style="list-style-type: none"> Gamber-Johnson <ul style="list-style-type: none"> Has with LIND power supply Vehicle Docks (dual pass-through) <ul style="list-style-type: none"> Gamber-Johnson <ul style="list-style-type: none"> Has with LIND power supply Replacement Digitizer Pen Tether 10.1" LCD Protective Film | <ul style="list-style-type: none"> CF-AA6413CM FZ-VZSU84U FZ-VZSU88U FZ-BNDLG1LL1ST1CG4 FZ-BNDLG1BATCHR FZ-LND3BAYG1 CF-LNDDC120 CF-LNDACDC90 CF-LNDMLDC90 FZ-WCG6111 FZ-BNDLG1ST1CG4 TBCG1A0NL-P TBCG1PFLIO-BLK-P TBCG1XSTP-P FZ-VEBG11U 7160-0486-00-P CF-H-PAN-702-P 7160-0486-02-P CF-H-PAN-702-2-P FZ-VNPG11U FZ-VNTG11U FZ-VPFG11U |
|--|--|

Please consult your reseller or Panasonic representative before purchasing.

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments.

¹ Approximate time. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other customer preferences. Battery testing results from MobileMark 2007.

² Bridge battery, magstripe reader, insertable SmartCard reader, contactless SmartCard reader and UHF RFID reader are mutually exclusive. Please note, USB 3.0 port cannot be accessed when the unit is equipped with the magstripe reader, but optional USB 2.0 port can be accessed.

³ GPS, Serial Dongle, Ethernet, MicroSD, 2nd USB port are mutually exclusive options.

⁴ Please refer to cleaning and maintenance instructions in the user guide.

⁵ 1GB = 1,000,000,000 bytes.

⁶ Total usable memory will be less depending upon actual system configuration.

⁷ The size of the VRAM cannot be set by the user and varies by operating system as well as size of RAM. Windows 7 max. VRAM is 1555MB.

⁸ Includes tall corner guards and rotating hand strap.

⁹ Requires software and activation to enable theft protection.

¹⁰ Length measurements do not include protrusions. Weight varies with options and digitizer pen.

¹¹ Accessories and Integrated Options may vary depending on your configuration. Visit Panasonic website for more accessories and details.

¹² Hazardous location certifications may not apply to all configurations. Consult your Panasonic representative for availability.



TOUGHPAD